


IMPELLER CROSS REFERENCE GUIDE



No	INSERT TYPE	
1	SLOTTED SHAFT PIN DRIVE	⊙
2	KEY DRIVE	○
3	SINGLE FLAT DRIVE	○
4	DOUBLE FLAT DRIVE	○
5	HEXA SPLINE DRIVE	⊙
6	SPLINE DRIVE(12)	⊙
7	SPLINE DRIVE(14)	⊙
8	SPLINE DRIVE(11)	⊙
9	SPLINE DRIVE(10)	⊙

JMP	DIMENSION			BLADES	INSERT TYPE	JABSCO	JOHNSON	NIKKISO	KASHIYAMA	SHERWOOD
	A	B	C							
6000	32	12	8	6	3	(2)1414-0001				
7000	39.7	19.2	12	6	1	22405-0001	09-808B			
7001	39.7	19.2	9.5	6	1	4528-0001	09-806B			9979
7013	39.7	19.2	12	6	3					8000
7050	51	22	12	6	1	653-0001	09-810B			
7051	51	22	12.7	6	1	673-0001	09-1026B			
7052	51	22	12.7	6	2	22799-0001				
7053	51	22	8	6	3	6303-0001	09-824P			
7054	51	22	12.7	6	3	Oberdorfer 6593				
7070	51	22	12	10	1	18653-0001				
7071	51	22	12.7	10	1	18673-0001				
7072	51	22	12.7	10	3					
7100	57	31.5	16	12	6	1210-0001	09-1027B	F15CBC	KP-30	
7110	57	20	12.7	12	2					10077
7136	57	48.2	16	12	6	13554-0001	09-812B			
7151	57.5	31.2	16	8	1			F15		
7162	62.5	22.2	16	12	2					
7172	62.5	22.4	16	12	2					9000
7192	62.5	32	16	12	2	18838-0001	09-701B			9959
7200	65	37	16	8	6	11979-0001				
7205	65	45	16	8	5			F20		
7300	65	41.5	15.8	12	2	18948-0001	09-702B			10615
7306	65	41.5	16	12	6				SP-60	
7352	65	51	15.8	12	2					15000
7356	65.3	50.4	16	12	6					
7376	65.8	80	25	12	6		09-821B			
7400	65	50	16	8	6	920-0001	09-1028B	F20CBC	SP-70	18200
7405	65	50	16	8	5					
7420	65	68	15.8	10	6	31130-0061			SP-130	
7426	65	50	15.8	10	6	17937-0001				
7436	65	50	15.8	10	6	YAMAHA 72X-12457-00				
7446	65	76	16	8	6	17018-0001				
7500	79	54	20	8	2			F25KBC		
7501	79	53.3	20	8	6					
7502	79	54	19	8	4					
7526	79	54	20	9	6				KP-100	
7556	80	75	20	9	6				SP-170	
7600	82.4	73.4	20	12	2	18958-0001	09-704B			17000
7608	82.4	73.4	20	12	8					27000
8000	95	63	25	9	6	836-0001	09-1029B	F40CBC	SP-200/220	
8001	95	63	25	9	4					
8002	95	63	25	9	5			F40	SPM-200	
8016	95	43	25	9	6				SP-150	
8100	95	63	25	12	6	17935-0001	09-819B			
8101	95	63	25	12	4					
8124	95	63	25.3	11	4					
8159	95	80	25	12	9					26000
8200	95	88.8	25	9	6	6760-0001	09-802B		SP-280	
8201	95	88.5	25	9	4					
8205	95	88.8	25	9	5					
8250	95	95	25	9	6				KP-300	
8300	95	88.8	25	12	4	17370-0001				
8301	95	88.8	25	12	6	17936-0001	09-814B			
8309	95.8	88.5	24	12	9					
8326	95	95	25	12	6	17938-0001				
8350	95	101.5	24	12	7		09-705B			18000
8359	95	101.5	24	12	9					29000
8400	100	100	25	9	6					
8406	100	100	25	10	6				SP-400	
8457	114.4	109.6	24	10	7					22000
8459	114.4	109.6	24	10	9					30000
8503	110	75.5	25	10	3			F50		
8506	110	75.5	25	10	6			F50S		
9000	117	88.5	25	9	4	18786-0001				
9001	117	88.5	25	9	6	18789-0001				
9100	128	101.5	36	12	6	31500-0001			SP-500	
9136	129	128	36	13	6				SP-600	
9202	128	101.5	38	6	2					
9206	128	101.5	36	6	6					
9212	128	101.5	34	6	2					
9500	132	31.5	25.4	18	2	15299-1000				